

TA906ADX Cat.6A Die-Cast 180° Keystone Jack (Slim Type)

Specification:

Qualified Screened Class E_A/Category 6A
 Permanent Link and Channel of ANSI/TIA-568-C.2
 IEC 60603-7-51
 ISO/IEC 11801 2nd edition
 Cenelec EN 50173-1

Electrical:

Current Rating: 1.5 Amps
 Insulation Resistance: 500 Mohms Minimum
 Contact Resistance: 20 mohms Maximum
 DC Resistance: 0.1 ohms Maximum

Mechanical:

Plug Insertion Life: 750 Cycles Minimum
 Plug & Jack Contact Force: 100 Grams Minimum
 Using FCC-Approved Plug
 Plug Retention Force: 30 lbs Minimum
 Temperature: -40° to 150°F (-40°C to 68°C)

Physicals:

Housing & Cap: Zinc Alloy Die-Casting
 Cover & holder: High Impact Flame Retardant Plastic,
 UL 94V-0 Rated
 Springshielded: 0.25 Thickness SUS301
 PCB: FR4, 1.6mm Thickness
 Jack Wiring: 0.42mm Thickness Phosphor Bronze
 Gold Over Nickel Plating
 Connector: Insulation Displacement Connector
 (IDC) Accept #23~26 AWG Solid Wire



TA906ADX



HT90X8