

Air Duster

Product Code: EADP

PRODUCT DESCRIPTION

Electrolube's Airduster aerosols of pure, compressed, inert gas are designed for the safe removal of dust and airborne contamination from very delicate or unaccessible areas of electrical and electronic equipment. **Electrolube's Airdusters** are non-flammable, non-CFC and non-HCFC products.

PRODUCT USE

This latest addition to Electrolube's airduster range offers increased power enabling **EADP** to be used to remove even stubborn dust and airborne contamination from all electrical and electronic equipment, e.g. computers, typewriters, control equipment etc. It can also be used on such items as cameras and Hi-Fi equipment. Airduster can also be used to evacuate air from the top of cans of paint etc. to stop skin forming. May also assist in drying operations after cleaning etc.

FEATURES

- * Pure compressed inert gas
- * Extremely high pressure removes contamination easily and quickly

TYPICAL PROPERTIES

Form:	Colourless Gas
Density (liquid):	1.176
Flashpoint:	None
Boiling Point:	-26.2°C
Ozone Depleting Potential:	0.00

TECHNICAL
DATA
SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



Air Duster – Page 2

DIRECTIONS FOR USE

This product should be used in a vertical position or at an angle of not greater than 60° to the vertical otherwise a freezing effect will result.

Caution Do not use an **Airduster** for prolonged blasts as the surface of the can will form frost.

PACKAGING

400ml Aerosol

ORDER CODE

EADP400

TECHNICAL
DATA
SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

