

規格 SPECIFICATIONS :

| | | |
|----------------------|--|--|
| 波 長 Wavelength | 630 ~ 650 nm (RED) | |
| 輸出功率 Output Power | 1 mW / 3 mW / 5 mW / each line | |
| 標線長度 Line Length | 1 M / 2 M / 3 M / each line | |
| 輸入電壓 Input Voltage | AC 90 ~ 260V to DC 5V Adaptor (PS1) or PS3 or PS5 | DC 24V |
| 操作溫度 Operating Temp. | - 10 ~ 50 °C | |
| 安全等級 Safety Class | Class IIIa / Class IIIb | |
| 使用壽命 Lifetimes | 20,000 小時 (hr) | |
| 外觀尺寸 Dimensions | D 25 × L 90 (mm) | |
| 重 量 Weight | 雷射頭 (Laser Body) 75 ± 5 公克 (g) / 固定座 (Bracket) 260 ± 5 公克 (g) | |
| 適用行業 Applications | <ul style="list-style-type: none"> ● 布料加工 Fabric processing ● 鐵材加工 Metal working ● 裁紙加工 Paper processing | <ul style="list-style-type: none"> ● 縫紉加工 Sewing processing ● 自行車加工 Bicycle processing ● 印刷品加工 Print processing |
| 備 註 Remarks | <p>1. 若未使用原廠設計之完整腳座固定雷射頭時,建議使用非金屬材質 (如:塑鋼、電木), 以隔絕雷射頭與機械設備的電位接觸。 If you do not use the original design of a complete mounting fixed to the laser head, recommend the use of non-metallic materials (such as: Plastic and bakelite), in order to cut off the laser head and the equipment conductive contact.</p> <p>2. 雷射光對人體眼睛的視網膜會造成傷害,使用操作時請勿直視光源。 Do not catch your sight with the beam. It may result in the harm to your eyes.</p> <p>3. 請勿自行調整或拆裝雷射頭上之零件(含螺絲),以避免損壞情況擴大,徒增不必要的維修成本。 Please do not adjust the laser head or removable parts (including screws), to avoid damage to expand, and inviting unnecessary maintenance costs.</p> | |

應用範例 Example :