





環保長效蓄光型夜光粉 產品一覽表


型號	粒徑(um)	發光能力(mcd/m ²)			
		10 min	60min	發光時間	
G-6B(黃綠)	65~85	725	120	> 12 hour	
G-6C(黃綠)	45~55	480	85		
G-6D(黃綠)	25~35	380	55		
G-6E(黃綠)	5~15	280	39		
G-6F(黃綠)	2~10	240	30		
G-4B(黃綠)	65~85	640	105		
G-4C(黃綠)	45~55	450	70		
G-4D(黃綠)	25~35	320	42		
G-4E(黃綠)	5~15	220	29		
G-4F(黃綠)	2~10	190	23		
G-2C(黃綠)	55~75	350	40		
G-2D(黃綠)	15~45	250	32		
B-5B(藍綠)	65~85	700	120		> 12 hour
B-5C(藍綠)	45~55	480	85		
B-5D(藍綠)	25~35	360	58		
B-5E(藍綠)	5~15	260	38		
B-4B(藍綠)	65~85	630	110		
B-4C(藍綠)	45~55	440	75		
B-4D(藍綠)	25~35	320	50		
SB-9B(天藍)	65~85	260	22	> 6 hour	
SB-9C(天藍)	45~55	220	18		
SB-9D(天藍)	25~35	180	15		
SB-9E(天藍)	5~15	140	12		

* 發光亮度測試條件：D65 標準光源，照度1000LX，激發10min。

* G-6B / G-4B / B-5B / B-4B / SB-9B無水性規格。

* G系列本體色： 黃綠光：

B系列本體色： 藍綠光：

SB系列本體色： 天藍光：