

線徑	內徑	長度	間隔縫	K值(mm/KG)	最大行程(mm)	最大荷重(KG)	有效圈數
3.5	20	60	6.4	1.860	31.79	59.13	6.06
3.5	20	80	6.4	1.395	44.72	62.39	8.08
3.5	20	100	6.4	1.116	57.65	64.34	10.10
3.5	20	120	6.4	0.930	70.58	65.64	12.12
3.5	26	60	9	1.187	36.20	42.98	4.80
3.5	26	80	10	0.962	52.26	50.26	5.93
3.5	26	100	8.5	0.684	63.83	43.66	8.33
3.5	26	120	9	0.594	79.40	47.14	9.60
3.5	33	60	13	0.827	40.27	33.32	3.64
3.5	33	80	12.5	0.602	55.50	33.40	5.00
3.5	33	100	12	0.466	70.42	32.84	6.45
3.5	33	120	10	0.338	81.89	27.72	8.89
4	20	60	5.5	2.859	26.74	76.44	6.32
4	20	80	7	2.483	42.91	106.53	7.27
4	20	100	7	1.986	55.64	110.50	9.09
4	26	60	8.5	1.926	32.80	63.17	4.80
4	26	80	9	1.502	47.38	71.18	6.15
4	26	100	8	1.109	58.67	65.08	8.33
4	26	120	8	0.924	72.00	66.56	10.00
4	33	60	12	1.314	37.00	48.62	3.75
4	33	80	12	0.986	52.00	51.25	5.00
4	33	100	12.5	0.813	67.76	55.09	6.06
4	33	120	12	0.657	82.00	53.88	7.50
4	40	60	15	0.928	39.37	36.53	3.16
4	40	80	14	0.659	54.22	35.75	4.44
4	40	100	15	0.557	70.95	39.50	5.26
4	40	120	14	0.440	85.33	37.51	6.67
4.5	20	60	6	4.758	25.29	120.30	5.71
4.5	20	80	6.3	3.670	37.67	138.24	7.41
4.5	20	100	6.3	2.936	49.33	144.85	9.26
4.5	26	60	8.7	3.100	30.55	94.69	4.55
4.5	26	80	8	2.202	42.20	92.92	6.40
4.5	26	100	8	1.761	55.00	96.88	8.00
4.5	26	120	8	1.468	67.80	99.52	9.60
4.5	33	60	12.5	2.148	35.12	75.44	3.53
4.5	33	80	11.5	1.516	48.50	73.54	5.00
4.5	33	100	12.5	1.289	64.53	83.17	5.88
4.5	33	120	11.5	1.011	77.25	78.09	7.50
4.5	40	60	13	1.323	35.57	47.07	3.43
4.5	40	80	13	0.992	50.43	50.05	4.57
4.5	40	100	14	0.839	66.68	55.96	5.41
4.5	40	120	12.5	0.643	79.24	50.93	7.06
5	20	60	5.5	6.825	21.43	146.25	5.71
5	20	80	5.5	5.119	31.90	163.31	7.62
5	20	100	5.2	3.978	40.98	163.02	9.80

線徑	內徑	長度	間隔縫	K值(mm/KG)	最大行程(mm)	最大荷重(KG)	有效圈數
5	20	120	6	3.575	55.45	198.25	10.91
5	26	60	8	4.432	26.92	119.32	4.62
5	26	80	8	3.324	39.23	130.40	6.15
5	26	100	8	2.659	51.54	137.05	7.69
5	26	120	8	2.216	63.85	141.48	9.23
5	33	60	12	3.147	32.35	101.80	3.53
5	33	80	11	2.221	45.00	99.95	5.00
5	33	100	11.3	1.810	59.33	107.39	6.13
5	33	120	10	1.388	70.00	97.17	8.00
5	40	60	16	2.341	35.71	83.59	2.86
5	40	80	13	1.505	47.78	71.89	4.44
5	40	100	14	1.271	63.68	80.92	5.26
5	40	120	13	1.003	76.67	76.90	6.67
6	26	60	7.5	8.676	21.33	185.10	4.44
6	26	80	6.8	6.170	30.50	188.18	6.25
6	26	100	7	5.013	41.85	209.78	7.69
6	26	120	7	4.178	52.62	219.80	9.23
6	33	60	9	5.325	24.00	127.81	4.00
6	33	80	10	4.260	38.00	161.89	5.00
6	33	100	10	3.408	50.50	172.12	6.25
6	33	120	9.8	2.805	62.43	175.10	7.59
6	40	60	11.5	3.786	27.43	103.85	3.43
6	40	80	11.5	2.840	40.57	115.21	4.57
6	40	100	13	2.467	56.42	139.17	5.26
6	40	120	12	1.947	68.00	132.41	6.67