


V型可變排量柱塞泵 V Series Axial Piston Pumps



常壓:175bar
瞬間:280bar

- 1.V型柱塞泵,以獨特設計斜盤變化角度功能,廣泛應用於各種場所。特殊設計,在全壓力區內,保持低噪音性能。
- 2.由多種控制方式整合,能形成系統,具有省能源、小型化、低成本功能等優點。
- 3.功率損失小、減低油溫上升、可選配較小型油箱。
- 4.廣泛應用於工具機、機床、鍛壓、塑膠成形機等。

1. Combining special internal designs and strict engineering disciplines has reduced noise level to new lows in whole pressure zones.
2. Depending on variety of application needs multiple optional unique control methods are available. It does not only reduce a number of unnecessary horses, pipes and control valves but also increase efficiency and save horsepower, and cost.
3. Less capacity reservoirs can be selected and applied because of performances of low pressure loss and less heat generation.
4. Wide application ranges: it is very suitable for machine tools, plastic injection molding machines, forging machines, other industrial machines and so on.

型號說明 Nomenclature

V 15 A 1 R S — **1001**

V: V:可變排量柱塞泵 variable displacement type

15: 規格 Ratings
15, 18, 23, 25, 38, 42, 50, 70, (cm³/rev)

A: 壓力調整範圍 Pressure adjusting
控制型式 Control type
A, B, C, CG, D, DG, E, EG, F, FG, G, GJ, GM, HL, HJ, HK, HQ

1: 迴轉方向 Shaft rotation
R 順時針方向 clock wise
L 逆時針方向 counter clock wise

R: 配管方向 Direction of pipe connections
無記號 兩側出油 side port
B 後方出油 axial port
B2 兩側出油加後方出油 4 connections for axial port

S: 軸心型式 Shaft type
無記號: S:SAE J498b
無記號 鍵式 Cylindric key
S 梅花軸(SAE J498b)

1001: 電壓 Voltage
配管牙型 Threads code
通軸規格 Thru drive & Design number 2nd pump
特殊規格編號 Links type
客戶需求編號 Customers demand

無記號: 標準品 Standard
X1 低壓母機專用 Low Pressure
Z 空轉洩壓型 Idling Relief

無記號: 標準型 Standard
A: 兩孔型 SAE A 2 bolt
針對 V15, V18 For V15, V18

無記號: 單泵 None: Single pump
C SAE AA, Φ50.8mm
D SAE A, Φ82.55mm
E SAE B, Φ101.6mm
F SAE C, Φ127mm
I Metric, Φ63mm
J Metric, Φ80mm
K Metric, Φ100mm
L Metric, Φ125mm

A	AC100V(50/60Hz)
B	AC110V(60Hz)
C	AC200V(50/60Hz)
D	AC220V(60Hz)
E	DC12V
F	DC24V

10	PT(RC)	管牙型 Pipe type
40	BSPP(G)	公制 Metric
50	NPT	英制 Inch
60	SAE(O-Ring)	英制 Inch
70	M□	公制 Metric

編號 Code	彈簧 Spring
無記號 None	標準7KG Standard pressure: 7kg
B	中壓14KG Middle pressure: 14kg
C	高壓21KG High pressure: 21kg

*針對HL型式專用
*This spring code is useful for HL type

1:0.8-6.9Mpa(8-70kgf/cm ²)
2:1.5-13.7Mpa(15-140kgf/cm ²)
3:2.0-20.6Mpa(20-210kgf/cm ²)
4:2.0-24.5Mpa(20-250kgf/cm ²)

編號 Code	型式 Type	齒數 Number of Teeth	螺距 Pitch	
			1500rpm	1800rpm
S	V15	13	16/32 DP	
S1	V18	9		
S2		11		
S	V23	13	16/32 DP	
S1	V25	15		
S3	V38	13加長 Lengthening		
S	V42			
S	V50	14	12/24 DP	
S1	V70	17		

規格表 Specifications

型式 Model	最高使用壓力 Max. Pressure kgf/cm ² (psi)	吐出量 Displacement cc/rev(in ³ /rev)	無負荷時之吐出量 Unloading Conditions l/min(GPM)		壓力調整範圍 Pressure Adj. Range kgf/cm ² (psi)	迴轉數(rpm) Input Speed Range		重量 Weight kg(lb)
			1500rpm	1800rpm		最低min	最高max	
V15A	250(3500)	15(0.90)	22.5(5.78)	27.0(7.05)	1:8~70(115~100) 2:15~140(210~2000) 3:20~210(280~3000) 4:20~250(280~3500)	500	1800	13(28.6)
V18A	250(3500)	17.8(1.09)	26.7(7.05)	32.0(8.45)				13(28.6)
V23A	250(3500)	23.0(1.40)	35.4(9.11)	41.4(10.94)				22(48.4)
V25A	210(3000)	25.0(1.52)	37.5(9.66)	45.0(11.60)				22(48.4)
V38A	250(3500)	37.8(2.31)	56.7(14.98)	68.0(17.96)				26(57.2)
V42A	210(3000)	42.0(2.56)	63.0(16.23)	76.0(19.58)				26(57.2)
V50A	210(3000)	51.5(3.14)	77.2(20.37)	92.7(4.49)				55(121)
V70A	210(3000)	69.7(4.25)	104.5(27.60)	125.4(33.13)				56(123.2)
V15A-V15A	250(3500)	15/15	22.5/22.5	27/27				28.5(62.7)
V23A-V23A	250(3500)	23.0/23.0	35.4/35.4	41.4/41.4				46.5(102.3)
V15A-V38A	250(3500)	15/37.8	22.5/34.5	27/68	41.5(91.3)			
V38A-V38A	250(3500)	37.8/37.8	56.7/56.7	68/68	54.5(119.39)			
V15A-V70A	210(3000)	15/69.7	22.5/104.5	27/125.4	71.5(157.3)			
V38A-V70A	210(3000)	37.8/69.7	56.7/104.5	68/125.4	84.5(185.9)			

控制方式 Control Type

名稱 Control Type	液壓符號 JIS Symbols	性能曲綫 Characteristics	特性 Feature
A型式： 壓力補償控制 Pressure Compensator Control			1.系統壓力增高接近調定限壓時，泵流量自動下降，壓力保持恒定。 2.流量及限壓壓力可手動調整。 1. When system pressure increase and reach preset pressure the flow decrease automatically and pressure maintain without changing. 2. Power and pressure can be adjusted manually.
B型式： 無段變速，靠外援油缸，流量可任意變化。 Multi-stage Flow & Single stage Pressure Control Type (With Cylinder)			1.流量可從0調到最大，從最大調到最小，做多段變化，壓力保持設定壓。 2.使機械在上升、下降具有緩動使用，可防止衝撞、震動，適合專用機、升降起重機械。 1. Flow can be adjusted from 0 to maximum and pressure can be maintaining at preset pressure. 2. Absorbing impact and vibration which are produced by up and down motions of actuators. It is suitable for lifting equipment etc.
C型式： 單泵兩段壓力，兩流量(自壓式) 2 stage Pressure & Flow Control Type			1.具低壓大流量，高壓小流量之高低壓泵功能，可選小功率之發動機。 2.系統壓力增高，接近預調的“PH”限壓時，泵的流量自動降到“QL” 3.壓力“PH，PL”及流量“QH，QL”可分別任意調整。 4.適用於空行程長，加壓行程短之機械，速度快，省馬力。 1. Low consumption electric motor can be selected to save energy because of the functions of high flow at low pressure and low flow at high pressure. 2. When pressure increase and reach preset pressure "PH", flow is reduced to "QL" 3. Pressure "PH" "PL", and Flow "QH" "QL" can be adjusted optionally. 4. It is applied to actuators requiring long unloaded or short loaded strokes. Speedy and horsepower efficient.
CG型式： 單泵遙控兩段壓力，兩流量(自壓式) 2 stage remote Pressure & Flow Control Type			1.同單泵兩段壓力，兩流量(自壓式)“C型”。 2.可做遙控調整壓力，並由遙控閥調整壓力範圍。 3.可配合油昇比例壓力閥，達成電控比例壓力控制。 1. The same function of "C" control type. 2. The pressure and the range can be adjusted remotely by the integrated remote pressure control valve. 3. Proportional Electro-hydraulic pressure control can be applied with YEOSHE proportional valve.
D型式： 低壓卸載壓力補償控制 Solenoid Controlled Pressure Compensating Type With Unloading Device			1.A型式壓力補償控制追加卸壓機能。 2.適用於卸壓時間長的情況。 3.系統停機時，通過泵的卸壓運轉，油溫和噪音可保持較低水平。 1. Same as Type A and unloading function added. 2. It is applied to systems requiring long term unloading operation. 3. When solenoid is turned off, pump operation under unloading condition maintains low noise level and oil heat generation.
DG型式： 低壓卸載遙控壓力補償控制 Solenoid Controlled Pressure Compensating Type With Unloading & Remote Device			1.同單泵兩段壓力，兩流量(自壓式)“D型”。 2.可做遙控調整壓力，並由遙控閥調整壓力範圍。 3.可配合油昇比例壓力閥，達成電控比例壓力控制。 1. The same function of "C" control type. 2. The pressure and the range can be adjusted remotely by the integrated remote pressure control valve. 3. Proportional Electro-hydraulic pressure control can be applied with YEOSHE proportional valve.

控制方式Control Type

名稱Control Type	液壓符號JIS Symbols	性能曲線Characteristics	特性Feature
E型式： 電控兩段壓力補償形式 Dual Pressure Control			<ol style="list-style-type: none"> 1. 依電磁換向閥，控制高低兩個不同的限壓壓力。 2. 適用於起動器在恒定速度下，設定兩段工作壓力時使用。 3. PL與PH閥可任選一方作為高壓。 <ol style="list-style-type: none"> 1. Preset high and low pressure can be controlled by switching directions of solenoid control valves. 2. This type is applied to actuators requiring 2 stage pressures with single speed. 3. One of "PL" and "PH" can be optionally be high pressure.
EG型式： 電控遙控兩段壓力補償形式 Dual & Remote Pressure Control			<ol style="list-style-type: none"> 1. 同電控兩段壓力補償形式“E”型。 2. 可做遙控調整壓力，並由遙控閥調整壓力範圍。 3. 可配合油昇比例壓力閥，達成電控比例壓力控制。 <ol style="list-style-type: none"> 1. The same function of "E" control type. 2. The pressure and the range can be adjusted remotely by the integrated remote pressure control valve. 3. Proportional Electro-hydraulic pressure control can be applied with YEOSHE proportional valve.
F型式： 電控單泵兩段壓力，兩段流量控制 2 flow-2 pressure p.c. by solenoid operated valve			<ol style="list-style-type: none"> 1. 依電磁換向閥控制低壓大流量及高壓小流量的功能。當電磁閥通電時，壓力升高至PH，流量降至QL。 2. 壓力PL，PH及流量QL，QH可任意調整。 3. 適用於快速近給轉變慢速進給之機床設備等。 <ol style="list-style-type: none"> 1. Actuators can be shifted slowly (high pressure low flow) and quickly (low pressure high flow) by switching directions of solenoid control valve. When solenoid valve turns on, pressure increase to "PH", and flow decrease to "QL". 2. Pressure "PL", "PH" and flow "QL", "QH" can be adjusted optionally. 3. This type is applied to actuator requiring operations of shift speed from high to low or low to high.
FG型式： 電控遙控單泵兩段壓力，兩段流量控制 2 flow-2 pressure p.c. by solenoid operated & remote value			<ol style="list-style-type: none"> 1. 同電控單泵兩段壓力，兩段流量控制“F”型。 2. 可做遙控調整壓力，並由遙控閥調整壓力範圍。 3. 可配合油昇比例壓力閥，達成電控比例壓力控制。 <ol style="list-style-type: none"> 1. The same function of "F" control type. 2. The pressure and the range can be adjusted remotely by the integrated remote pressure control valve. 3. Proportional Electro-hydraulic pressure control can be applied with YEOSHE proportional valve.
G型式： 遠程壓力補償形式 Remote pressure compensator control			<ol style="list-style-type: none"> 1. 同壓力補償“A”形式。 2. 可做遙控調整壓力，並由遙控閥調整壓力範圍。 <ol style="list-style-type: none"> 1. The same function of "A" control type. 2. Pressure can be adjusted remotely by the integrated remote pressure control valve.
GJ型式： 疊式比例壓力控制 Proportional Pressure with interface			<ol style="list-style-type: none"> 1. 與GM控制相同介面與功能。 2. 配裝比例壓力閥於調節閥NG6介面上，形成電控比例控制，節省能源系統。 <ol style="list-style-type: none"> 1. Same as Type "GM" and proportional valve added. 2. The proportional valve is installed on the NG6 interface to reach Proportional Electro-hydraulic control to save energy.

控制方式 Control Type

名稱 Control Type	液壓符號 JIS Symbols	性能曲綫 Characteristics	特性 Feature
GM型式: 層式遙控控制 (不含調壓閥) Remote Interface (Not include pilot valve)			<ol style="list-style-type: none"> 1. GM控制的調節閥上方有一個NG6的介面。可直接安裝調壓閥於介面，調節遙控閥所需壓力。亦由控制板直接設定壓力。 2. 反應速度較快，提供壓力更為穩定。 3. 可採用手動或電液比例控制調節。 <ol style="list-style-type: none"> 1. GM control with a NG6 interface, supply an installation for pilot valve to prove the operating pressure. The pressure setting can be set directly from the control panel of the machine. 2. The remote pressure compensator responds faster and offers more stable pressure. 3. The adjustment can also be manual or proportional pressure control.
HL型式: 負載感應控制 Load Sensing Compensator			<ol style="list-style-type: none"> 1. 靠流量控制閥前後差壓一定值，控制油泵吐出量。與比例換向閥並用，能形成理想的系統省能源功能。 2. 能控制負載壓力一定時，而流量依節流閥改變，油泵自動感應回饋系統吐出的恒定流量，能達到低油溫省能源功能。 <ol style="list-style-type: none"> 1. The pump outlet can be controlled by the setting pressure value of flow control valve. An ideal energy conservation system can be configured by combining the proportional directional control. 2. When setting pressure value, flow is changed depending on throttle valve. The sensing flow feedback function can reach to low oil heat generation and saving energy.
HJ型式: 負載感應+比例壓力控制閥 Load Sensing & Proportional Electro-hydraulic Pilot Relief Valve			<ol style="list-style-type: none"> 1. 此為HL形式泵浦所具備之特性外，再增加比例壓力控制。 2. 裝配電磁比例壓力後，依入力電流比例控制，達到省能源、省馬力功能 <ol style="list-style-type: none"> 1. Same as Type "HL" and proportional pressure function added. 2. Supplied with proportional electro-hydraulic pilot relief valve can reach to horse-saving and energy-saving.
HK型式: 負載感應+比例壓力+比例流量 Proportional Electro-hydraulic Load Sensing Type			<ol style="list-style-type: none"> 1. HK型式變量柱塞泵與比例閥構成一體，依照比例壓力、比例流量、電流大小控制，及依照負載的大小提供系統所需要的壓力與流量，節省不必要的能源消耗。當待機時柱塞泵吐出流量近似零，電機功率損耗輸出亦近似零，當系統壓力升高到設定值時，柱塞泵的流量會自動減少，只補充系統所需流量，而壓力是維持不變的，故大幅減低油溫上升，節省不必要的能源浪費。 2. 液泵與一般葉片或齒輪泵+PQ閥所配合的油路相互比較，約可以節省電力30%~50%能源。油箱液壓油容量亦可較小，省電又環保的最佳設計。 <ol style="list-style-type: none"> 1. HK type supplies the system pressure and flow depending on the proportional pressure and flow, voltage, and load value to save the energy. When in waiting circle, the outlet displacement and horse power loss are close to zero. When pressure reaches to preset value, the flow decrease to the min., and the pressure is constant to reach low oil heat generation and energy loss. 2. HK type can save 30%~50% energy compare to vane pump and gear pump+PQ valve. It is an energy-saving and environmental design.
HQ型式: 負載感應控制+比例流量控制 Load-sensing Proportional Flow control			<ol style="list-style-type: none"> 1. 此為HL型式泵浦所具備之特性外，再增加比例流量控制。 2. 同比例流量閥控制，藉電信輸入以調節泵浦排量。及電控模組之控制提供所需流量。 <ol style="list-style-type: none"> 1. Same as Type "HL" and proportional flow function added. 2. The proportional flow control allows the adjustment of the pumps output flow with an electrical input signal. Supplied and adjusted the displacement by the electronic control module.