


17.0" open frame Touch Monitor

LCD Technology	Active matrix TFT color LCD 7" diagonal screen size 280 x 1024 addressable pixels 0.264 mm x 0.264 mm Pixel Pitch 300 cd/m ² (typ.) Brightness 800:1 (typ.) Contrast Ratio Tr+Tf: 5ms (typ.) L/R=80°/80°, U/D=80° / 80° Viewing Angle
Display Resolution	1280 pixels (H) x 1024 lines (V)
Touch Panel	5W Resistive or CAP .SAW Type with RS232 or USB interface connector
Active Display Area	337.9 (H) x 270.3 (V) mm
Displayable Color	16.7millions colors
Horizontal Scan	30kHz to 80kHz
Vertical Refresh	50 Hz to 75Hz
Pixel Frequency	110MHz
Compatibility	<ul style="list-style-type: none"> Ⓞ IBM & VESA VGA 640 x 350, 70 Hz 640 x 400, 70 Hz 720 x 400, 70 Hz 640 x 480, 60 Hz Ⓞ VESA VGA 640 x 480, 72/75 Hz Ⓞ VESA SVGA 800 x 600, 56/60/72/75 Hz Ⓞ VESA XGA 1024 x 768, 60/70/75 Hz Ⓞ VESA SXGA 1280 x 1024, 60 Hz
Input Signal	Analog RGB 0.7 Vp-p
Auto-adjustment	Yes
I/O Connectors	<ul style="list-style-type: none"> Ⓞ DC power in Ⓞ VGA in D-sub 15 pin DVI (option) Ⓞ RS232 or USB
User Controls	<ul style="list-style-type: none"> Ⓞ Power On/Off Button Ⓞ External Auto-Adjustment Ⓞ OSD Control items: Auto Tune, Auto Contrast, Brightness, Contrast, H Position, V Position, Detail Adjust, Color Temperate, OSD Setup, Image Setting, Recall

Power Saving	VESA DPMS standard (4 mode)
Power Consumption	36 watt (max.), < 3 watt (stand by mode)
Agency approval	FCC-B, CUL, CE-B, CCC, BSMI,
Environmental operating temperature	5 ° ~ 35°C
Humidity	80% maximum
Storage	ⓄTemperature: -20°~60°C / -4°~140°F ⓄHumidity: 95% maximum
Dimension (W*H*D)	390mm * 361mm * 48.7mm
Weight	N.W. 4.6Kg G.W. 5.8Kg

The specification of the product is for reference only. It might be changed without any notice.
PRODUCT WITHOUT ALUMINUM FRONT PANEL
