


19.0" touch open frame Monitor

LCD Technology	Active matrix TFT color LCD <ul style="list-style-type: none"> ● 19" diagonal screen size ● 1280 x 1024 addressable pixels ● 0.294 mm x 0.294 mm Pixel Pitch ● 300 cd/m² (typ.) Brightness ● 700:1 (typ.) Contrast Ratio ● Tr+Tf: 6ms (typ.) ● L/R=70°/70°, U/D=70° / 60° Viewing Angle
Display Resolution	1280 pixels (H) x 1024 lines (V)
Touch Panel	5W Resistive or CAP .SAW Type with RS232 or USB interface connector
Active Display Area	376.3 (H) x 301.1 (V) mm
Displayable Color	16.7millions colors
Horizontal Scan	30kHz to 80kHz
Vertical Refresh	50 Hz to 75Hz
Pixel Frequency	110MHz
Compatibility	© IBM & VESA VGA 640 x 350, 70 Hz 640 x 400, 70 Hz 720 x 400, 70 Hz 640 x 480, 60 Hz © VESA VGA 640 x 480, 72/75 Hz © VESA SVGA 800 x 600, 56/60/72/75 Hz © VESA XGA 1024 x 768, 60/70/75 Hz © VESA SXGA 1280 x 1024, 60 Hz
Input Signal	Analog RGB 0.7 Vp-p
Auto-adjustment	Yes
I/O Connectors	© DC power in © VGA in D-sub 15 pin.DVI (option) © RS232 or USB
User Controls	© Power On/Off Button © External Auto-Adjustment © OSD Control items: Auto Tune, Auto Contrast, Brightness, Contrast, H Position, V Position, Detail Adjust, Color Temperate, OSD Setup, Image Setting, Recall

Power Saving	VESA DPMS standard (4 mode)
Power Consumption	36 watt (max.), < 3 watt (stand by mode)
Agency approval	FCC-B, CUL, CE-B, CCC, BSMI,
Environmental operating temperature	5 ° ~ 35°C
Humidity	80% maximum
Storage	Ⓞ Temperature: -20° ~ 60°C / -4° ~ 140°F Ⓞ Humidity: 95% maximum
Dimension (W*H*D)	426mm * 354mm * 48.7mm
Weight	N.W. 3.9Kg G.W. 5.1Kg

* PRODUCT WITHOUT ALUMINUM FRONT PANEL