



307010001
Analog Installation SP



307010082
Analog Installation BD

超細麥克風線,由於細微,所以在屏蔽、對絞技術上必需特別加強,否則極易受到干擾
SUNRISE的超細麥克風線使用了纏繞與編織等多種工藝,可以滿足95%以上的屏蔽要求!

Superfine microphone cable. Due to thinner type, thus the technology of shielding and twisted pair should be particularly strengthened. Otherwise, it's easily to be interfered. SUN RISE superfine microphone cable is using many technologies like spiral and braiding, etc. It can satisfy over 95% shielding requirement.



3070200018
Analog Installation SP

這是為了立體平衡式音頻而設計的線纜,一次可以傳送L,R兩個通道
也可以用來製造Y-CODE

This is designed for stereo balanced audio cable.

It can transmit L & R channels once.

Also can be used to produce Y-CODE



307020018
Analog Broadcast Studio Installation AL+DW TC@shield

為了壓克力或玻璃的透明講桌所設計的透明線,雙併設計讓線纜可以黏貼在邊緣產生隱形效果
讓講桌被攝影機攝入時看起來簡潔不混亂!

It is designed for use glass or acrylic podium microphone cable

The dual-channel design, let sticky paste becomes feasible,

This will allow the podium at ceremony, more beautiful, because the cable is "invisible"!

ITEM NO.型號	3070100001	3070100004	3070100082	3070200018	3070200042
JACKET COLOR 顏色	3 COLORS	8 COLORS	4 COLORS	BLACK	TRANSPARENT
CONDUCTOR.導體	2*(10/0.10)PE	2*(20/0.12)PE	2*(10/0.10)PE	2*(10/0.12)PE 2CH	2*(20/0.10+PE1.1) 2CH
JACKET OD.外徑	3.3mm	4.3mm	3.0mm	4.0X 8.0 mm	3.0X6.0mm
WIRE INFORMATION 線材資料	2*(10/0.10+250D NYLON FIBER+PE1.0) +COTTON YARN+ SP 40/0.10	2*(20/0.12)PE + SP 80/0.10	2*(10/0.10+500D +PE0.85)+BD 16X5/0.10	2*(10/0.12)PE+ SP 30/0.12	2*(20/0.10+PE1.1) +DW7/0.20TC+AL-FOIL
MAIN CONDUCTOR AWG 主要導體直徑	29AWG 0.0785mm ²	24AWG 0.226mm ²	29AWG 0.0785mm ²	27AWG 0.113mm ²	25AWG 0.16mm ²

ELECTRICAL PERFORMANCE 電氣性能					
Cond.D.C.R. ohm/1Km 導體電阻/1km	Less than 256	77+2%	262 +/-110%	168.09	121.01
Shield D.C.R. ohm/1Km 屏蔽層電阻/1km	Less than 59	Less than 29	Less than 30	58.49	90.76
Nom.Cap.(pF/m)between conductors.導體間電容量	Less than 94	Less than 100	Less than 103	62.86	68.1
Nom.Cap.(pF/m)between conductors./shield 導體/屏蔽間電容量	Less than 99	Less than 122	Less than 109	130.5	143.2
Voltage Breakdown 絕緣承 受電壓	300V	300V	300V	300V	300V

MECHANICAL PERFORMANCE 機械性能					
Flex Life Number of times load 500g +/-30°搖晃壽命次數 負載 500g 角度 +/-30°	Better than 27000	Better than 4500	Better than 31600	---	---
Tensile Strength (26° C,65%RH)拉伸斷裂力量	Better than 30kgf	Better than 47kgf	Better than 23.9	---	---
Applicable Temperature 建議工作溫度	-20°~ +60°C (-4°~ +140°F)	-20°~ +60°C (-4°~ +140°F)	-20°~ +60°C (-4°~ +140°F)	-20°~ +60°C (-4°~ +140°F)	-20°~ +60°C (-4°~ +140°F)
Peak Temperature 極限工作溫度	-40°~ +70°C (-40°~ +158°F)	-40°~ +70°C (-40°~ +158°F)	-40°~ +70°C (-40°~ +158°F)	-40°~ +70°C (-40°~ +158°F)	-40°~ +70°C (-40°~ +158°F)
100Mweight/100M 重量(kg)	1.4±0.2	2.7±0.2	1.4±0.2	4.0±0.2	2.2±0.2

COLOR & ORDER INFORMATION 色彩與訂購資訊

黑 BLACK	3070100001	3070100004	3070100082
紅 RED	3070100005	3070100006	3070100083
橙 ORANGE	3070100003	3070100007	3070100008
黃 YELLOW	3070100008	3070100009	3070100010
綠 GREEN	3070100011	3070100084	3070100148
藍 BLUE			
紫 PURPLE			
白 WHITE	3070100002	3070100011	3070100084
金 GOLDEN			

Audio cable