規格 SPECIFICATIONS:

波 長 Wavelength	630 ~ 650 nm (RED)
輸出功率 Output Power	1 mW / 2 mW / 3 mW
標線長度 Line Length	< 15 cm / < 30 cm / < 45 cm / each line
輸入電壓 Input Voltage	乾電池 LITHIUM CR123 DC3 V (Battery Only)
操作溫度 Operating Temp.	- 10 ~ 50 °C
安全等級 Safety Class	Class ∏ / Class ∭a
使用壽命 Lifetimes	> 15,000 小時 (hr)
外觀尺寸 Dimensions	D 20 × L 88 (mm)
重 量 Weight	45±5公克(g)(Without Battery)/60±5公克(g)(With Battery)
適用行業 Applications	 ● 布料加工 Fabric processing ● 鐵材加工 Metal working ● 報紙加工 Print processing ● 裁紙加工 Paper processing ● 経紉加工 Sewing processing
備 註 Remarks	1. 若未使用原廠設計之完整腳座固定雷射頭時,建議使用非金屬材質 (如:塑鋼、電木),以隔絕雷射頭與機械設備的電位接觸. If you do not use the original design of a complete mounting fixed to the laser head, recommend the use of non-metallic materials (such as: Plastic and bakelite), in order to cut off the laser head and the equipment conductive contact. 2. 雷射光對人體眼睛的視網膜會造成傷害,使用操作時請勿直視光源. Do not catch your sight with the beam. It may result in the harm to your eyes. 3. 請勿自行調整或拆裝雷射頭上之零件(含螺絲),以避免損壞情況擴大,徒增不必要的維修成本. Please do not adjust the laser head or removable parts (including screws), to avoid damage to expand, and inviting unnecessary maintenance costs.

應用範例 Example:



