

★ Absolute Clean Engine Protection Oil Series

RAZATEK

Product Information
Speed Series



1L
24 L / box

Absolute Clean
ULTRA NO.1
Engine Protection Oil

FULLY SYNTHETIC	For High Speed	For Turbo	For DPF
NO Heavy Metal	NO Teflon	NO MoS2	NO Carbon

SPEED
POWER
CLEAN

- ABSOLUTE CLEAN WITHOUT ANY CARBON.
- WITHOUT ANY OIL SLUDGE.
- FOR GASOLINE AND DIESEL ENGINE.
- FOR TURBO / DPF ENGINE REQUIREMENTS.
- FOR HIGH-SPEED DRIVING
- HIGH TEMPERATURE RESISTANCE >300 °C

**No Heavy Metal, No Teflon, No MoS2, No Sulfide,
No Molybdenum disulfide.**

★Viscosity at @40°C 59.65 @100°C 10.52



RAZATEK

Product Information
Treatment Series



Gold NO.5
General

1L
24 L / box

Absolute Clean
Engine Protection Oil **Gold NO.5**

- | | |
|-----------------------------------------------|-------------------------|
| ★ Fully Synthetic | ★ Cure engine oil loss |
| ★ Cure pressure loss | ★ Cure fuel loss |
| ★ Clean engine carbon | ★ Clean oil sludge |
| ★ Extend components life | ★ Recovery engine power |
| ★ Ash% < 0.001% (General oil Ash%=0.1%~1.5%) | |
| ★ High temperature resistance >300 °C. | |

- FOCUS ON TREATMENT OF ENGINE OIL LOSS & ENGINE PRESSURE LOSS.
- ABSOLUTE CLEAN WITHOUT ANY CARBON & OIL SLUDGE.
- FOR GASOLINE AND DIESEL ENGINE.
- FOR TURBO CHARGE ENGINE REQUIREMENTS.
- FOR DPF EQUIPMENT.
- EXCELLENT HIGH TEMPERATURE RESISTANCE.

**No Heavy Metal, No Teflon, No MoS2, No Sulfide,
No Molybdenum disulfide.**

★Gold NO.5 Viscosity at @40°C 130.72 @100°C 18.85



Engine Guarder (engine oil additive series)

RAZATEK

Product Information
Additive Series

Engine Guarder

Motor Oil Additive

**The savers for engine's
vibration & noise**



50ML
Concentrate Version

1L
24 L / box

Only 5~10 minutes, the oil additive can improve noise and vibration of engine very fast!

**No Heavy Metal, No Teflon, No MoS2, No Sulfide,
No Molybdenum disulfide.**

- For Gasoline and Diesel engine.
- Do not add into ATF oil.
- Add when the car engine is warm.

Super Smooth!

- Reduce engine noise and vibration.
- Reduce over 50% engine friction.
- Increase heat dissipation of oil.
- Strongly intensity oil membrane .
- Increase acceleration of engine.
- Extend motor oil life.
- Energy saving.



悅竣股份有限公司

TEL:04-23313488 FAX:04-23313477

台灣台中市霧峰區光明路 90 號

經理 張皓硯 0982-251255 / 0928-010727 e-mail: potter@razatek.com.tw