



1. ORDERING INFORMATION

(CUSTOMER'S SPECIFICATION ARE WELCOME)

MD - 0708 U - XXT - S - C
 (1) (2) (3) (4) (5) (6)

- (1) TYPE (MD: INSERT MOLDED COILS;
MDS: SMD MOLDED COILS);
- (2) STYLE (07=SIZE,08=HEIGHT);
- (3) U: UNSHIELDED STYLES;
S: WITH SHIELD CAN STYLES;
- (4) NUMBER OF TURNS;
- (5) S: SPACEWOUND C: CLOSEWOUND;
- (6) CORE MATERIAL: C: COPPER CORE.

2. INDEX

PART NO.	NUMBER OF TURNS RANGE	INDUCTANCE RANGE(nH)	Q RANGE
MD-0605U-XXT-C-C	1.5T-4.5T	9.8~47.0	30-80
MD-0605S-XXT-C-C		8.9~37.8	25-60
MD-0508U-XXT-S-C	1.5T-6.5T	13~86	50
MD-0508S-XXT-S-C		11~60	50
MD-0708U-XXT-C-C	1.5T-8.5T	17~209	50
MD-0708S-XXT-C-C		15~151	50-60
MD-0711U-XXT-S-C	1.5T-8.5T	16~152	50-60
MD-0711S-XXT-S-C		14~115	50-60
MD-0711U-XXT-C-C	1.5T-10.5T	15~190	30-60
MD-0711S-XXT-C-C		15~185	30-60
MD-0913U-XXT-S-C	1.5T-5.5T	15~86	50
MD-1014U-XXT-C-C	1.5T-13.5T	23~540	40~80
MD-1014S-XXT-C-C		20~410	35~70
MDS-0605U-XXT-C-C	1.5T-4.5T	10.5~46.7	50-80
MDS-0605S-XXT-C-C		9.3~35.9	40-70